









## COQISOL : réponse à la réglementation thermique, traitement des ponts thermiques et de l'étanchéité à l'air



| Plafond                                                                           | Produit                          | Référence             | Ø 80                        | Ø 100                       | Ø 130                       | Ø 150                       | Ø 180                       |
|-----------------------------------------------------------------------------------|----------------------------------|-----------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
|  | Plaque distance sécurité étanche | <b>PDSE ... TP3E</b>  | 30 080 720<br><b>57,93</b>  | 30 100 720<br><b>60,92</b>  | 30 130 720<br><b>64,33</b>  | 30 150 720<br><b>71,55</b>  | 30 180 720<br><b>78,67</b>  |
|  | Coquille isolante h 350          | <b>COQI350...TP3E</b> | 30 080 721<br><b>121,52</b> | 30 100 721<br><b>126,62</b> | 30 130 721<br><b>132,49</b> | 30 150 721<br><b>138,36</b> | 30 180 721<br><b>141,18</b> |
|                                                                                   | Coquille isolante h 500          | <b>COQI500...TP3E</b> | 30 080 726<br><b>139,76</b> | 30 100 726<br><b>145,60</b> | 30 130 726<br><b>156,50</b> | 30 150 726<br><b>159,10</b> | 30 180 726<br><b>162,33</b> |
|  | Collier de soutien réhaussé      | <b>CSR ... TP3E</b>   | 30 080 787<br><b>37,72</b>  | 30 100 787<br><b>37,72</b>  | 30 130 787<br><b>37,72</b>  | 30 150 787<br><b>37,72</b>  | 30 180 787<br><b>44,26</b>  |

| Plafond rampant                                                                    | Produit                                                    | Référence                                                                                                                                                                     | Ø 80                                                                         | Ø 100                                                                        | Ø 130                                                                        | Ø 150                                                                        | Ø 180                                                                        |
|------------------------------------------------------------------------------------|------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------|
|    | Plaque distance sécurité étanche rampant                   | <b>PDSER40...TP3E</b><br>DE 10 À 40 %<br><b>PDSER80...TP3E</b><br>DE 41 À 80 %<br><b>PDSER120...TP3E</b><br>DE 81 À 120 %                                                     | 30 080 730<br>30 080 731<br>30 080 732<br><b>68,40</b>                       | 30 100 730<br>30 100 731<br>30 100 732<br><b>68,40</b>                       | 30 130 730<br>30 130 731<br>30 130 732<br><b>68,40</b>                       | 30 150 730<br>30 150 731<br>30 150 732<br><b>68,40</b>                       | 30 180 730<br>30 180 731<br>30 180 732<br><b>89,40</b>                       |
|  | Coquille isolante rampant                                  | <b>COQI ... TP3E 40</b><br>DE 10 À 40 %<br><b>COQI ... TP3E 70</b><br>DE 41 À 70 %<br><b>COQI ... 3E 100</b><br>DE 71 À 100 %<br><br><b>COQI ... 3E 120</b><br>DE 101 À 120 % | 30 080 722<br>30 080 723<br>30 080 724<br><b>148,50</b><br><br><b>178,21</b> | 30 100 722<br>30 100 723<br>30 100 724<br><b>178,21</b><br><br><b>178,21</b> | 30 130 722<br>30 130 723<br>30 130 724<br><b>178,21</b><br><br><b>215,34</b> | 30 150 722<br>30 150 723<br>30 150 724<br><b>178,21</b><br><br><b>215,34</b> | 30 180 722<br>30 180 723<br>30 180 724<br><b>178,21</b><br><br><b>215,34</b> |
|  | Plaque de propreté pour plaque PDSE rampant Blanc (P 9020) | <b>PPPDSE40... E</b><br>DE 10 À 40<br><b>PPPDSE80... E</b><br>DE 41 À 80 %<br><b>PPPDSE120... E</b><br>DE 81 À 120 %                                                          | 30 080 745<br>30 080 746<br>30 080 747<br><b>96,87</b>                       | 30 100 745<br>30 100 746<br>30 100 747<br><b>96,87</b>                       | 30 130 745<br>30 130 746<br>30 130 747<br><b>96,87</b>                       | 30 150 745<br>30 150 746<br>30 150 747<br><b>96,87</b>                       | 30 180 745<br>30 180 746<br>30 180 747<br><b>126,61</b>                      |

| Traversée de mur                                                                    | Produit                                   | Référence          | Ø 80                        | Ø 100                       | Ø 130                       | Ø 150                       | Ø 180                       |
|-------------------------------------------------------------------------------------|-------------------------------------------|--------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
|  | Kit Traversée de Mur                      | <b>KTM ... TZ</b>  | 20 080 129<br><b>341,52</b> | 20 100 129<br><b>359,41</b> | 20 130 129<br><b>377,56</b> | 20 150 129<br><b>387,64</b> | 20 180 129<br><b>404,75</b> |
|   | Kit de traversée de mur Conduit extérieur | <b>KTM ... PGI</b> | 37 080 730<br><b>452,14</b> | 37 100 430<br><b>485,73</b> | -                           | -                           | -                           |

| Ventilation habillage                                                               | Produit                         | Référence  | Ø 80 | Ø 100 | Ø 130                      | Ø 150 | Ø 180 |
|-------------------------------------------------------------------------------------|---------------------------------|------------|------|-------|----------------------------|-------|-------|
|  | Grille de ventilation* (90 cm²) | <b>GVH</b> |      |       | 55 000 278<br><b>25,53</b> |       |       |

\* Produit vendu à l'unité avec précadre ; pour être conforme à l'Avis Technique, prévoir 2 grilles (ventilation haute et basse).

| Solution hors RT2012                                                                | Produit                               | Référence             | Ø 80                       | Ø 100                      | Ø 130                      | Ø 150                      | Ø 180                      |
|-------------------------------------------------------------------------------------|---------------------------------------|-----------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
|  | Plaque distance sécurité non ventilée | <b>PDSNV ... TP3E</b> | 30 080 741<br><b>57,93</b> | 30 100 741<br><b>60,92</b> | 30 130 741<br><b>64,33</b> | 30 150 741<br><b>71,55</b> | 30 180 741<br><b>78,67</b> |
|  | Plaque réhausse distance sécurité     | <b>RPDS ... TP3E</b>  | 30 080 743<br><b>24,98</b> | 30 100 743<br><b>24,98</b> | 30 130 743<br><b>24,98</b> | 30 150 743<br><b>26,59</b> | 30 180 743<br><b>26,59</b> |