

GAMME DE BARRES D'APPUI / GRAB RAIL RANGE

Droite
/ Straight

135°

Main courante TL
/ Carril TLCharge max. 150 kg
/ Maximum weight loadExiste en plusieurs coloris
/ Other available coloursFixations invisibles
/ Hidden fixingsInstallation facile
/ Easy installationNettoyage facile
/ Easy cleaning

OUTILS / TOOLS



INSTRUCTIONS / INSTRUCTIONS

FR

Barre d'appui murale. AVERTISSEMENT : fixations non fournies. Suivez les instructions pour vous assurer que la barre est fermement fixée. Assurez-vous d'utiliser des fixations adaptées à votre support.

- Garantie à vie
- Charge maximale 150kg
- Plusieurs coloris
- Fixations invisible
- Installation facile
- Nettoyage facile

EN

Grab rail.
WARNING: Fixing screws not included. Follow the instructions to make sure that the rail is firmly fixed. Attach this grab rail to a surface using fixings matched to the type of surface and the loading conditions to be applied.

- Lifetime guarantee
- Maximum weight load 150kg
- Other available colours
- Hidden fixings
- Easy installation
- Easy cleaning

DROITE / STRAIGHT

135°

MAIN COURANTE TL / CARRIL TL

The diagrams illustrate the following steps:

- Preparation of the track end, including the installation of a stop block and a guide pin.
- Insertion of the track into the wall or ceiling structure.
- Securing the track with a screw and a cover cap.
- Installation of the track into a corner or T-junction.
- Assembly of the track with a sliding door mechanism, including the installation of a roller and a guide pin.
- Final assembly of the track with a sliding door mechanism, including the installation of a roller and a guide pin.
- Installation of the track into a corner or T-junction.
- Final assembly of the track with a sliding door mechanism, including the installation of a roller and a guide pin.
- Installation of the track into a corner or T-junction.
- Final assembly of the track with a sliding door mechanism, including the installation of a roller and a guide pin.
- Installation of the track into a corner or T-junction.
- Final assembly of the track with a sliding door mechanism, including the installation of a roller and a guide pin.