







Accessoires

Accessoires	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180	Ø 200	Ø 230	Ø 250
	Support plancher	SP ... DP	45 080 281 39,52	45 100 281 39,97	45 130 281 44,62	45 150 281 44,62	45 180 281 46,88	45 200 281 46,88	45 230 281 46,88	45 250 281 79,58
	Raccord calo intérieur et extérieur	RACCI ... DP	45 080 213 93,39	45 100 213 93,39	45 130 213 135,50	45 150 213 135,50	45 180 213 180,76	45 200 213 180,76	45 230 213 180,76	45 250 213 230,51
	Raccord bas flexible sur buse (même diamètre)	RF ... BU	45 080 244 44,31	45 100 244 44,31	45 130 244 49,17	45 150 244 49,17	45 180 244 54,21	45 200 244 61,23	45 230 244 61,23	45 250 244 70,93
	Raccord flexible	RF ...	45 080 043 18,48	45 100 043 18,48	45 130 043 19,21	45 150 043 20,59	45 180 043 21,84	45 200 043 22,58	45 230 043 22,58	45 250 043 24,70
	Raccord flexible à visser pour conduit émaillé	RFV EM ...	45 080 152 48,77	45 100 152 48,77	45 130 152 54,09	45 150 152 54,09	45 180 152 59,62	45 200 152 67,33	-	-
	Adaptateur sur buse même Ø	A ...	45 080 065 17,15	45 100 065 17,15	45 130 065 17,84	45 150 065 17,84	45 180 065 17,84	45 200 065 20,27	45 230 065 20,27	45 250 065 21,32
	Réduction sur buse*	RB .../...BU	45 080 018 47,09	45 100 018 47,09	45 130 018 48,98	45 150 018 48,98	45 180 018 48,98	45 200 018 56,97	45 230 018 56,97	45 250 018 62,47
	Té de purge vers inox (même Ø)	TPI ...	45 080 073 69,67	45 100 073 69,67	45 130 073 72,49	45 150 073 81,49	45 180 073 93,19	45 200 073 113,47	45 230 073 113,47	45 250 073 146,80
	vers émaillé**	Ø émaillé ↓ TPI ... - ... EM ↑ Ø flexible	45 080 273 95,52	45 100 273 101,91	45 130 273 109,44	45 150 273 118,46	45 180 273 130,14	45 200 273 150,41	-	-
	Té avec tampon d'obturation vers inox (même Ø)	TPTO ...	45 080 191 68,32	45 100 191 68,32	45 130 191 71,04	45 150 191 78,18	45 180 191 88,53	45 200 191 108,87	45 230 191 108,87	45 250 191 143,86
	vers émaillé**	Ø émaillé ↓ TPTO ... - ... EM ↑ Ø flexible	45 080 291 94,16	45 100 291 100,55	45 130 291 107,99	45 150 291 115,15	45 180 291 125,49	45 200 291 145,84	-	-
	Jaquette de finition*** H = 500 mm	JF 500 ... DP- ... EM (Même Ø)	45 080 220 134,00	45 100 220 148,89	45 130 220 165,42	45 150 220 172,03	45 180 220 180,17	45 200 220 188,17	45 230 220	45 250 220
	Jaquette de finition*** H = 1000 mm	JF 1000 ... DP- ... EM (Même Ø)	45 080 222 174,19	45 100 222 193,55	45 130 222 215,06	45 150 222 223,65	45 180 222 234,21	45 200 222 244,62	-	-
	Rosace pour jaquette de finition***	ROS ... JDP	45 080 221 51,38	45 100 221 57,08	45 130 221 63,43	45 150 221 68,03	45 180 221 70,82	45 200 221 73,67	-	-
	support plancher pour jaquette de finition	SP ... TZ	20 130 081 40,77	20 150 081 41,47	20 180 081 42,36	20 200 081 43,62	20 250 081 44,64	-	-	-
	Bride murale Alu flexible isolé	BM ... DP	45 080 202 20,93	45 100 202 20,93	45 130 202 24,56	45 150 202 24,56	45 180 202 26,54	45 200 202 26,54	45 230 202 26,54	45 250 202 29,27

* À prévoir uniquement entre le raccord flexible du tubage et la buse de l'appareil.

** Possibilité de réduction vers Émaillé 3 Ø maxi.

*** Disponible en blanc (RAL 9020) ou noir mat (RAL 9019)