

Partial storage heating

Series TT KS-N



TT KS-N

Low partial thermal-storage heater with individually weld-on fins, powdercoated surface, white RAL 9003, only 70 mm depth, infinitely variable built-in thermostat controls your room temperature, connecting lead 1.5 m with plug, 230 V~, incl. stands. **Mobile version.**
IP 20



TT KS-N DSM

Low partial thermal-storage heater , in addition with DSM thermostat. The DSM thermostat can be controlled via the DSM interface (to be ordered separately, see page 107) via the Internet using the free TECHNOTHERM APP. Separate temperatures and various time programs can be set for each room (see page 8-9). With electronic room temperature control and weekday regulation. Detection of open window. Adaptive start control. Internet option (see page 107).



Model	Power [kW]	Dimensions B x H x T [mm]	Weight [kg approx.]	Order number	Price [Euro]
TT-KS 800 N	0,80	680 x 340 x 70	21,00	450 308 965	730,41
TT-KS 1200 N	1,20	980 x 340 x 70	24,50	450 312 965	940,88
TT-KS 1600 N	1,60	1280 x 340 x 70	34,50	450 316 965	1136,57
TT-KS 2000 N	2,00	1580 x 340 x 70	38,00	450 320 965	1162,74

Discount group TT_200

All units can also be ordered in IPX4 for a 51,95 Euro surcharge.

Model	Power [kW]	Dimensions B x H x T [mm]	Weight [kg approx.]	Order number	Price [Euro]
TT-KS 800 N DSM	0,80	680 x 340 x 70	21,00	450 308 975	812,33
TT-KS 1200 N DSM	1,20	980 x 340 x 70	24,50	450 312 975	1017,11
TT-KS 1600 N DSM	1,60	1280 x 340 x 70	34,50	450 316 975	1205,97
TT-KS 2000 N DSM	2,00	1580 x 340 x 70	38,00	450 320 975	1231,00

Discount group TT_200

All units can also be ordered in IPX4 for a 51,95 Euro surcharge.