






CONDUITS CONCENTRIQUES



BÛCHE
OU GRANULÉS

EFFICIENCE


Supports et maintiens

	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Support mural Inox 5 à 20 cm	SMI 5-20 ... SLCD	45 180 056 200,56	45 200 056 211,13	45 230 056 231,24	45 250 056 253,99	45 280 056 260,63
	Support mural Galva 5 à 20 cm	SM ... SLCD	45 180 055 82,90	45 200 055 95,91	45 230 055 108,12	45 250 055 120,33	45 280 055 122,28
	Collier mural Inox	CMI ... SLCD	45 180 175 40,54	45 200 175 41,42	45 230 175 44,84	45 250 175 48,29	45 280 175 49,55
	Réglette murale 5 à 20 cm	RCM 5-20 ... SLCD	45 180 134 43,82		45 230 134 43,82		
	Collier de soutien	CS ... TP3E	30 080 782 31,52	30 100 782 32,55	30 130 782 33,47	30 150 782 33,87	30 180 782 36,79
	Support plancher	SP ... SLCD	45 180 081 44,82	45 200 081 46,16	45 230 081 46,83	45 250 081 47,22	45 280 081 54,78
	Maintien au toit	SAT ... SLCD	45 180 165 73,41	45 200 165 77,08	45 230 165 80,65	45 250 165 84,21	45 280 165 84,52

Accessoires plafond

Finitions plafond	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Rosace plafond (Blanc P 9020)	ROS ... TP3E	30 080 748 63,43	30 100 748 68,03	30 130 748 70,82	30 150 748 79,21	30 180 748 87,61
	Finition plafond ronde hauteur 26 cm (Blanc P 9020)	FP 260 ... EF 80 PGI	-	30 100 776 235,12	30 130 776 235,12	30 150 776 235,12	-




Raccordement intérieur




Noir P 9030	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Élément droit de finition H = 25 cm	NOIR (P 9019)	21 080 065	21 100 065	21 130 065	21 150 065	21 180 065
		BLANC (P 9020)	21 080 065	21 100 065	21 130 065	21 150 065	21 180 065
	Élément droit de finition H = 45 cm	EDP 250 ... TZ-... EM	103,40	114,71	125,70	130,79	135,93
		NOIR (P 9019)	21 080 015	21 100 015	21 130 015	21 150 015	21 180 015
	Rosace de finition	BLANC (P 9020)	21 080 015	21 100 015	21 130 015	21 150 015	21 180 015
		EDP ... TZ- ... EM	166,80	185,32	205,92	214,20	224,33
	Rosace de finition	NOIR (P 9019)	20 080 047	20 100 047	20 130 047	20 150 047	20 180 047
		ROS EDP 150 TZ	51,38	57,08	63,43	68,03	70,82
	Té 90° Piquage Therminox	TE 90 ... TI TP3E	30 080 450 252,21	30 100 450 274,53	30 130 450 296,72	30 150 450 316,42	30 180 450 375,69
	Adaptateur Buse Étanche (Noir P 9034 - Hte T°)		A EF 80 BU 30 080 096-9034 34,26	A EF 100 BU 30 100 096-9034 43,32	A EF 130 BU 30 130 096-9034 47,74	A EF 150 BU 30 150 096-9034 57,13	A EF 180 BU 30 180 096-9034 66,01
	Adaptateur Buse Étanche recoupable (Noir P 9034 - Hte T°) H : 250 mm	A RECOUP EF ... BU H250	30 080 041-9034 59,36	30 100 041-9034 61,93	30 130 041-9034 71,73	30 150 041-9034 83,09	30 180 041-9034 93,65
		A RECOUP EF ... BU H500	30 080 042-9034 61,97	30 100 042-9034 68,75	30 130 042-9034 81,26	30 150 042-9034 91,17	30 180 042-9034 97,48
	Té 90° Fumée Inox piquage simple avec trappe de visite latérale	T 90 ... 9030 TP3E	30 080 457-9030 558,73	30 100 457-9030 578,78	30 130 457-9030 596,70	30 150 457-9030 616,77	30 180 457-9030 638,24
		S AIR ... 9030 TP3E	30 080 058-9030 283,84	30 100 058-9030 297,33	30 130 058-9030 314,91	30 150 058-9030 336,54	30 180 058-9030 354,12



* Préciser à la commande le diamètre de la prise d'air (Ø80, Ø100, Ø125).

** Permet le réglage d'un Té fumée de 0,8 m à 1,15 m à l'axe. Existe aussi en hauteur 600 mm (réglage de 0,3 m à 0,55 m)

COQISOL : réponse à la réglementation thermique, traitement des ponts thermiques et de l'étanchéité à l'air



Plafond	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Plaque distance sécurité étanche	PDSE ... TP3E	30 080 720 57,93	30 100 720 60,92	30 130 720 64,33	30 150 720 71,55	30 180 720 78,67
	Coquille isolante h 350	COQI350...TP3E	30 080 721 121,52	30 100 721 126,62	30 130 721 132,49	30 150 721 138,36	30 180 721 141,18
	Coquille isolante h 500	COQI500...TP3E	30 080 726 139,76	30 100 726 145,60	30 130 726 156,50	30 150 726 159,10	30 180 726 162,33
	Collier de soutien réhaussé	CSR ... TP3E	30 080 787 37,72	30 100 787 37,72	30 130 787 37,72	30 150 787 37,72	30 180 787 44,26

Plafond rampant	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Plaque distance sécurité étanche rampant	PDSER40...TP3E DE 10 À 40 % PDSER80...TP3E DE 41 À 80 % PDSER120...TP3E DE 81 À 120 %	30 080 730 30 080 731 30 080 732 68,40	30 100 730 30 100 731 30 100 732 68,40	30 130 730 30 130 731 30 130 732 68,40	30 150 730 30 150 731 30 150 732 68,40	30 180 730 30 180 731 30 180 732 89,40
	Coquille isolante rampant	COQI ... TP3E 40 DE 10 À 40 % COQI ... TP3E 70 DE 41 À 70 % COQI ... 3E 100 DE 71 À 100 % COQI ... 3E 120 DE 101 À 120 %	30 080 722 30 080 723 30 080 724 148,50 178,21	30 100 722 30 100 723 30 100 724 178,21 178,21	30 130 722 30 130 723 30 130 724 178,21 215,34	30 150 722 30 150 723 30 150 724 178,21 215,34	30 180 722 30 180 723 30 180 724 178,21 215,34
	Plaque de propreté pour plaque PDSE rampant Blanc (P 9020)	PPPDSE40... E DE 10 À 40 PPPDSE80... E DE 41 À 80 % PPPDSE120... E DE 81 À 120 %	30 080 745 30 080 746 30 080 747 96,87	30 100 745 30 100 746 30 100 747 96,87	30 130 745 30 130 746 30 130 747 96,87	30 150 745 30 150 746 30 150 747 96,87	30 180 745 30 180 746 30 180 747 126,61

Traversée de mur	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Kit Traversée de Mur	KTM ... TZ	20 080 129 341,52	20 100 129 359,41	20 130 129 377,56	20 150 129 387,64	20 180 129 404,75
	Kit de traversée de mur Conduit extérieur	KTM ... PGI	37 080 730 452,14	37 100 430 485,73	-	-	-

Ventilation habillage	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Grille de ventilation* (90 cm²)	GVH			55 000 278 25,53		

* Produit vendu à l'unité avec précadre ; pour être conforme à l'Avis Technique, prévoir 2 grilles (ventilation haute et basse).

Solution hors RT2012	Produit	Référence	Ø 80	Ø 100	Ø 130	Ø 150	Ø 180
	Plaque distance sécurité non ventilée	PDSNV ... TP3E	30 080 741 57,93	30 100 741 60,92	30 130 741 64,33	30 150 741 71,55	30 180 741 78,67
	Plaque réhausse distance sécurité	RPDS ... TP3E	30 080 743 24,98	30 100 743 24,98	30 130 743 24,98	30 150 743 26,59	30 180 743 26,59